

410 D-LOK HELICOPTER HOIST HOOK



Description

The D-LOK incorporates an automatic dual-lock latch gate design for ultimate safety. The double lock gate provides security to prevent accidental openings, while allowing the latch gate to be operated quickly and easily with one hand. The hoist hook features a large ring volume for multiple equipment rings, and will accept rings over one inch in diameter. Integral utility eye (#410 only) allows attachment of tag/guide line. Hook is constructed entirely of stainless steel for strength and corrosion resistance.

The D-LOK Hoist Hook eliminates all problems associated with the current double rescue hook, such as inadvertent engagement (including the snagging of fingers on the small hook), and self-release (ring roll-out). The LSC D-LOK Hoist Hook exceeds the load test requirement for the double rescue hook (MS-18027-2A), and is available with seven (7) attachment options to fit all current hoist installations.

AVIOTECH Srl

Sede operativa: Viale Pio XI, 103 – 89133 Reggio Calabria – Italy - Tel./Fax (+39) 0965.598134

www.aviotechsrl.it - info@aviotechsrl.it

Capitale Sociale € 12.750,00 i.v. C. F. - Partita IVA 03053151209 - n. REA: RC-194046




#410 & #411 D-Lock Helicopter Hoist Hook

D-LOK Helicopter Hook incorporates an automatic dual-lock latch gate designed for ultimate safety. The hook can be used easily with one hand and the double gate feature prevents accidental openings. This hook eliminates problems associated with inadvertent engagement and self release. Multiple end configurations are available to fit all current hoist installations. The #411 is the exact same as the #410, but without the body utility eye.

#410-A

Thread: .500-20 UNF-3A
End Configuration: Slot



#410-G / #411-G

Thread: .500-20 UNF-3A
End Attachment: Swivel



Configuration Options			
Thread Size	End Configuration / Attachment	Overall Shaft Length (Inches)	LSC Part No.
.500-20 UNF-3A	Slot	1.000"	410-A / 411-A
.437-20 UNF-3A	Pin Hole	1.312"	410-E / 411-E
.500-20 UNF-3A	Pin Hole	1.000"	410-F / 411-F
.500-20 UNF-3A	Pin Hole w/ Swivel	1.000"	410-G / 411-G

Specifications

Weight	~ 1.5 LBS	Proof Load Test:	2,100 LBS	Material:	Stainless Steel
Working Load Limit (WILL)	600 LBS For applications grater than 600 LBS contact LSC	Cleaning:	Fresh water rinse after exposure to saltwater environment		
Maintenance:	Regular lubrication with a light machine oil	Inspection:	Visual, prior to and after each use		

For more information view the catalog page or contact LSC